



Gasmeter DX4015

Gasmeter DX4015 is a portable FTIR gas analyzer designed for on-site measurements at low concentrations in ambient air. Typical usage areas include environmental research and industrial hygiene. The sample cell can be heated up to 50 °C. Sample cell absorption path length is selected according to the application.

System specifications

Measuring principle	Fourier transform infrared, FTIR
Multigas capability	Simultaneous analysis of up to 50 gas compounds
Response Time	Typically < 120 s
Power supply	115 / 230 V 50 / 60Hz Power consumption: Average 150 W, maximum 300 W
Analysis Software	Calcmeter (Required operating system Windows 7 or 10)
Data Connection	9-pole D-connector for RS-232 Analyzer is connected to an external computer via RS-232C cable. The external computer controls Gasmeter. Remote control connection for Portable sampling unit.
Sample pump	Integrated
Sample gas filtration	Minimum 2 µm particulate filtration.
Gas fittings	Sample in: 6 mm Swagelok, stainless steel Sample out: 8 mm Swagelok, stainless steel Interferometer purge: 6 mm Swagelok stainless steel
Enclosure	Dimensions: 390 x 445 x 164 mm Material: Aluminum
Weight	13.9 kg
Product compliance	CE, UKCA
Spectrometer	Resolution: 4/8 cm ⁻¹ Detector: Thermoelectrically cooled MCT Beamsplitter: Antireflection coated ZnSe Wave number range: 900 - 4 200 cm ⁻¹
Sample cell	Structure: Multi-pass, path length 9.8 m Material: Gold coated aluminum Mirrors: Fixed, protected gold coating Volume: 0.4 liters Temperature: 50 °C, maximum

Operating and storage conditions

Sample gas pressure	Ambient
Sample gas flow rate	2 – 10 l/min
Storage temperature	-20 to 60 °C, non-condensing
Operating temperature	Long term 5 to 30 °C, short term 0 to 40 °C

Performance specifications

Zero-point drift	< 2 % of measuring range per zero-point calibration interval
Sensitivity drift	None
Linearity deviation	< 2 % of measuring range
Temperature drift	< 2 % of measuring range per 10 K temperature change
Pressure influence	1 % change of measuring value for 1 % sample pressure change. Ambient pressure changes measured and compensated
Background measurement interval	24 hours, with nitrogen (5.0 or higher N ₂ recommended)

Gasmeter Technologies Oy

STREET ADDRESS:
Mestarintie 6
01730 Vantaa, Finland

TEL: +358 9 7590 0400
EMAIL: contact@gasmeter.fi

WEB: www.gasmeter.com
VAT NO: FI26818038

