

# Meticulously Measure, Confidently Calibrate

Gas Flow Calibration Solutions



[www.thomsongroup.com.au](http://www.thomsongroup.com.au)

 **MesaLabs**

## Mesa Labs specializes in gas flow calibration solutions to ensure defensible data.

### Why Mesa's Defender™ 500 Series?

- + High accuracy. Calibrators in Mesa's Defender Series are backed by Proven DryCal technology and have a reading uncertainty of less than 1%.
- + Durability. All DryCal calibrators are field-proven and have provided IH professionals with reliable performance for decades.
- + Real-time flow data. Calibrator flow data is captured in real time with our DryCal Pro software, directly uploaded to a PC and exported to a Microsoft environment.
- + Convenient mail-in factory calibration. An annual NIST-traceable calibration by Mesa's ISO-accredited facility provides a defensible audit trail and full refurbishment.
- + Trusted accreditation. Mesa Labs is a fully accredited ISO-17025 facility with a 0.08% Scope of Accreditation for gas flow by NVLAP of NIST.



When it comes to portable primary calibrators, our Defender 500 Series provides you with the flexibility and dependability you need, enabling you to focus on what matters most: defending lives.

# Get to know the Defender

Model	Defender 510 Volumetric Primary Flow Standard	Defender 520 Enhanced Volumetric Primary Flow Standard	Defender 530+ Standardized and Volumetric Primary Flow Standard
Flow Ranges	Low: 5-500 ccm Medium: 50-5,000 ccm High: 300-30,000 ccm	Low: 5-500 ccm Medium: 50-5,000 ccm High: 300-30,000 ccm	Low: 5-500 ccm Medium: 50-5,000 ccm High: 300-30,000 ccm
Volumetric Accuracy	1%	1%	0.75%
Standardized Accuracy	N/A	N/A	1%
User Selectable Measurement Units:	Volumetric	mL/min, L/min, cc/min, cf/min	mL/min, L/min, cc/min, cf/min
	Standardized	N/A	N/A
	Temperature	N/A	°C °F
	Pressure	N/A	mmHg, PSI, kPa
Pressure Accuracy	N/A	+ 3.5 mmHg (typical) + 7.0 mm (max)	+ 3.5 mmHg (typical) + 7.0 mm (max)
Temperature Accuracy	N/A	+ 0.8 °C (typical) + 1.3 °C (max)	+ 0.8 °C (typical) + 1.3 °C (max)
Industry Applications	Industrial Hygiene, Air Quality		Manufacturing, Air Quality, Personal Gas Sampling
Pressure and Suction Fittings	1/4" ID Hose Barb		1/4" ID Swagelok® compression fittings, 3/8" fittings on High Model

Looking for the Definer? The Defender 530+ is a direct replacement and offers the same high-accuracy and portability.

## START SIMPLE.

Turn the Defender on, connect it to your pump and begin taking measurements. It's that simple. Instantly calibrate your gas flow using Quick Start – there is no preparation involved, no messy soap bubble solutions. Defender's many user-selectable options make customizing your calibrations easy, giving you exactly what you need in the format you prefer.

# Defender Service from Mesa Labs

All calibration equipment needs periodic maintenance to ensure accuracy and traceability to comply with monitoring regulations. As the manufacturer of the Defender, Mesa Labs is the only laboratory in the United States that can repair and adjust the instrument if required. We are also a fully-accredited ISO-17025 lab with NIST-traceable flow standards that have an industry-leading accuracy of 0.08%.

## What Our Factory Service Includes:

- + Complete disassembly, inspection, cleaning and repair
- + Battery testing and replacement as needed
- + Firmware and hardware upgrades
- + Temperature and pressure sensor calibration
- + Flow calibration along with necessary adjustments
- + NIST-traceable certificate with pre/post (As-Found/As-Left) data
- + Calibration Warranty: 6 months from the date of service

## Why Choose Mesa Labs Over Third-Party Calibration:

- + Third-party labs cannot adjust your DryCal instrument
- + They cannot reset calibration points, perform repairs with authorized parts, update firmware/hardware, or replace batteries
- + Our calibration uses Met-Lab standards with 4:1 accuracy ratio (0.25% accuracy)
- + Direct NIST traceability through dimensional, time, temperature and pressure measurement
- + NVLAP-accredited with an exceptional  $\pm 0.08\%$  uncertainty for gas flow calibrations, ensuring industry-leading precision and traceability.

A Mesa factory calibration provides a defensible audit trail and ensures your DryCal instrument receives the proper care and maintenance required for precision measuring applications.

For service requests: contact us at [customerservice@mesalabs.com](mailto:customerservice@mesalabs.com)  
 For technical support: contact us at [dcsupport@mesalabs.com](mailto:dcsupport@mesalabs.com)

## Ordering Information

Part # 200-510L:	Defender 510 Low
Part # 200-510M:	Defender 510 Medium
Part # 200-510H:	Defender 510 High
Part # 200-520L:	Defender 520 Low
Part # 200-520M:	Defender 520 Medium
Part # 200-520H:	Defender 520 High
Part # 200-530+:	Low Defender 530+ Low
Part # 200-530+:	Medium Defender 530+ Medium
Part # 200-530+:	High Defender 530+ High



Learn more at [mesalabs.com](https://mesalabs.com)