



Model 751H

Portable High Performance Zero Air System



A portable, fully self-contained source of high purity zero air for dilution calibrators, the Model 751H is ideal for use with sensitive analyzers in ambient background and trace level applications.

- High Performance CO / hydrocarbon scrubber
- Long life scrubbers for SO₂, NO, NO₂, O₃, NH₃ and H₂S
- Rugged traveling case with wheels and retractable handle
- Dew point indicator
- Automatic water drain
- Once/year maintenance interval
- Two-year warranty



Model 751H Specifications

■ Output	10 SLPM at 30 psig
■ Max Delivery Pressure	30 psig
■ Dew Point	Less than -20°C
■ Dryer	Regenerative heatless with lifetime of greater than 5 years
■ Output Concentration	SO ₂ < 0.025 ppb H ₂ S < 0.025 ppb NO < 0.025 ppb NO ₂ < 0.025 ppb NH ₃ < 0.025 ppb O ₃ < 0.3 ppb CO < 10 ppb HC < 0.25 ppb
■ Compressor	Single-cylinder, internal long-life, oil-less piston pump
■ Power Requirements	110V-120V, 60Hz (320W) 220V-240V, 50Hz (425W)
■ Operating Temperature Range	5 - 40°C
■ Dimensions (HxWxD)	9" x 22" x 13.8" (229 x 559 x 351 mm)
■ Weight	47 lbs (21.3 kg)

Specifications subject to change without notice. All specifications are based on constant conditions.



www.thomsongroup.com.au



9970 Carroll Canyon Road ■ San Diego, CA 92131
Ph. 858-657-9800 Fax 858-657-9816
Email api-sales@teledyne.com

For more information about the Teledyne API family of monitoring instrumentation products, call us or visit our website at:

www.teledyne-api.com

© 2018 Teledyne API
Printed documents are uncontrolled. SAL000081D
(DCN 7975) 08.29.18

