

PRODUCT BROCHURE

HALO H2™

TRACE-LEVEL HYDROGEN ANALYZER



Designed for trace-level hydrogen analysis, the HALO H2 offers:

- Low parts-per-billion (ppb) detection capability with Standard Model
- **NEW:** Low-Range Model with parts-per-trillion (ppt) detection limits in inert gases
- Extremely fast speed of response
- Wide dynamic range
- Absolute measurement (freedom from need for calibration gases)
- Low maintenance and cost of ownership
- Direct measurement in many matrices, including oxygen

Leading Choice for Ultra-high Purity Gas Users

Detect gas quality upsets before they damage your process. Using Tiger Optics' HALO H2 hydrogen analyzer, you can verify H₂ impurity levels with high accuracy, drift-free stability and instantaneous response. You will find our system exceptionally easy and fast to install, and effortless to maintain, with built-in zero verification. Its robust design – free of moving parts – results in an analyzer that has a high Mean Time Between Failure (MTBF) rate and a very low Cost of Ownership (CoO).

With its patented catalytic conversion technique, utilizing a minute amount of oxygen to cleanly and safely convert hydrogen to moisture, the HALO H2 offers a fully laser-based solution for continuous quality control of your process.

Specifications

Performance

Operating range:	See table on next page
Detection limit (LDL, 3σ/24h):	See table on next page
Precision (1σ, greater of):	\pm 0.75% or 1/3 of LDL
Accuracy (greater of):	\pm 4% or LDL
Speed of response:	To be determined
Environmental conditions:	10°C to 40°C, 30% to 80% RH (non-condensing)
Storage temperature:	-10°C to 50°C

Gas Handling System and Conditions

Wetted materials:	316L stainless steel, 10 Ra surface finish
Leak tested to:	1 x 10 ⁻⁹ mbar l / sec
Gas connections:	1/4" male VCR
Sample inlet pressure:	10 – 125 psig (1.7 – 9.6 bara)
Sample flow rate:	0.5 slpm (\pm 20%) (Standard Model)
Sample gases:	Most inert matrices
Gas temperature:	Up to 60°C
Utility gas supply	See below for required gas, ~15 sccm, 20 – 125 psig

Dimensions & Weight

Standard sensor:	H x W x D 8.73 x 19.0 x 23.6 in (222 x 483 x 599 mm)
Standard sensor weight:	45 lbs (20.4 kg)

Electrical and Interfaces

Platform:	Max Series analyzer
Alarm indicators:	2 user programmable, 1 system fault, Form C relays
Power requirements:	100 – 240 VAC, 50/60 Hz
Power consumption:	450 Watts max.
Signal output:	Isolated 4–20 mA
User interfaces:	5.7" LCD touchscreen, 10/100 Base-T Ethernet, USB, RS-232, RS-485, Modbus TCP (optional)
Data storage:	Internal or external flash drive
Certification:	CE Mark

Standard Model (requires 1% O₂, 99% N₂ mixture or CDA utility gas*)

Performance, H₂	Range	LDL (3σ)	Precision (1σ) @ zero
In Nitrogen:	0 – 500 ppm	8.0 ppb	3.0 ppb
In Argon:	0 – 200 ppm	6.0 ppb	2.0 ppb
In Helium:	0 – 125 ppm	4.0 ppb	1.5 ppb
In Neon:	0 – 140 ppm	4.0 ppb	1.5 ppb

CDA Model (requires pure N₂ diluting/utility gas[†])

Performance, H₂	Range	LDL (3σ)	Precision (1σ) @ zero
In Clean Dry Air (CDA):	0 – 5000 ppm	80 ppb	30 ppb

Low-Range (LR) Model

Performance, H₂	Range	LDL (3σ)	Precision (1σ) @ zero
Inert Gas (requires 1% O ₂ , 99% N ₂ mixture or CDA utility gas* [‡])			
In Nitrogen:	0 – 20 ppm	0.3 ppb	0.1 ppb
In Argon:	0 – 9 ppm	0.13 ppb	0.05 ppb
In Helium:	0 – 4.0 ppm	0.10 ppb	0.04 ppb

*Gas supply purity requirements: <10 ppm H₂O, <0.1 ppm H₂

[†]Gas supply purity requirements: <1 ppm H₂O, <1 ppb H₂

[‡]Requires inert-gas-specific Zero Gas Panel and Linear Fit Mode

Contact us for additional analytes and matrices.
U.S. Patent # 7,277,177 • U.S. Patent # 7,255,836

GAIN REAL-TIME INSIGHT INTO YOUR PROCESS

Process Insights delivers premium analytical sensors, analyzers, instrumentation, software and solutions that are mission-critical to keep your operations, personnel, and the environment safe. Our commitment to customer satisfaction is evident through our diverse range of products, programs, and services, designed to accommodate various budgets and application needs.

CENTERS OF EXCELLENCE | PROVIDING PROVEN SOLUTIONS

Process Insights – The Americas

14400 Hollister Street, Suite 800B, Houston, TX 77066, USA +1 713 947 9591

Process Insights – EMEA


ATRICOM, Lyoner Strasse 15, 60528 Frankfurt, Germany +49 69 20436910

Process Insights – APAC

Wujiang Economic and Technology, Development Zone, No. 258 Yi He Road, 215200 Suzhou, Jiangsu Province, China +86 400 086 0106

For a complete range of products, applications, systems, and service options, please contact us at:
info@process-insights.com

For a complete list of sales & manufacturing sites, please visit:
<https://www.process-insights.com/about-us/locations/>



REVOLUTIONIZING MEASUREMENT

EVERYWHERE™